

Name of the document	Document nr.	Page
Declaration of confirmity	CPR1098	1 of 3
Wooden panels of spruce, painted with mud paint		
Prepared by	Number of edition	
Michaela Pfeiffer	1	
Approved by	Recplaces edition	Date of edition
Lars Kristen Holst	-	2022-10-28

DECLARATION OF CONFIRMITY - CPR1098

1. Product group and identification

External panel of spruce painted with red and black mud paint, thickness ≥22 mm.

2. Product information

Sawn, planed or profiled wooden panels with or without battens that meet the requirements of the harmonized standard EN 14915.

For additional or more detailed information about the delivered product, in addition to what is stated below, see the package specification or any attached commercial document.

3. The intended use of the product

External panel for walls and suspended ceilings that can be mounted horizontally or vertically.

4. Manufacturer

Company: Moelven Wood AB

Adress: Box 8006, 650 08 Karlstad, Sweden

Telephone: +46 10 122 50 50

E-mail: order.woodab@moelven.se

Webbsite: www.moelven.com

5. System for assessment of continuous control of the construction product's performance System 3 in AVCP.

6. Certification and stated performance

The product is produced according to the harmonized standard EN 14915.

The notified body DBI (identification number 0845) has carried out fire tests to check fire growth rate, flammability, and smoke growth. DBI has issued a classification report in accordance with EN 13501–1.

The specified standard that is followed has no replacement standard for the UK, but also applies to complying with the UKCA.







Name of the document	Document nr.	Page
Declaration of confirmity	CPR1098	2 of 3
Wooden panels of spruce, painted with mud paint		
Prepared by	Number of edition	
Michaela Pfeiffer	1	
Approved by	Recplaces edition	Date of edition
Lars Kristen Holst	-	2022-10-28

7. Declared performance

Essential characteristics		Declared values		
Reaction to fire		Fire class		
	Euroclass D-s2,d0 (according to EN 13501-1			
	Substrate			
	Mounting	Minimum density [kg/m3]	Fire class (EN 13501-1)	
	With ventilated or non-ventilated air gap or without air gap	38 (thickness min 22 mm)	A1	
Thermal conductivity	18,8 (according to EN 14915)			
Application	E - External (according to CEN TS 15912)			
Intened area of use	W - Wall and C - Cielings			
Wood species	PCAB (spruce)			
Durability	4 (according to EN 350-2)			
Density	>440 kg/m ³	>440 kg/m ³		
Sound absorption	0,10/0,30 (according to EN 14915)			
Water vapor permeability	20 (wet)/50 (dry) (according to EN 14915)			
Release of formaldehyde	E1			
Content of pentachlorophenol	NPD (no performance detected)			
Hazardous substances	NPD (no performance detected)			
Resistant to fixing	NPD (no performance detected)			





Name of the document	Document nr.	Page
Declaration of confirmity	CPR1098	3 of 3
Wooden panels of spruce, painted with mud paint		
Prepared by	Number of edition	
Michaela Pfeiffer	1	
Approved by	Recplaces edition	Date of edition
Lars Kristen Holst	-	2022-10-28

8. Additional technical documentation

The property of the product declared in section no.1 and 2 is in accordance with the property stated in section no.7. This declaration of performance is prepared under the responsibility of the manufacturer specified in Section No. 4.

Karlstad 2022-10-28

Lars Kristen Holst, manager product management



