

<i>Documentname</i> Declaration of performance Machine or visually strength graded structural timber	<i>Document no.</i> 137- 20190422	<i>Page</i> 1 of 2
<i>Prepared by</i> Odd Midtmoen	<i>Version</i> 1	
<i>Approved by</i> Per Skreden	<i>Replaces edition</i>	<i>Date</i> 2019-04-22

DECLARATION OF PERFORMANCE DOP-20190501-137

1. Productgroup and identification

Strength graded structural timber with rectangular cross section

2. Construction products

Machine strength graded structural timber which fulfills the requirements according to EN 14081. For further information or detail about product than given here, please see Pack Specification, Delivery Note or Invoice.

3. Intended use of the construction product

For load-bearing purposes in construction works designed according to Eurocode 5 (EN 1995) and for other uses where the strength and stiffness of the structure is essential.

4. Producer

Company: Moelven Industrier ASA
Address: Industrivegen 2
2390 Moelv
Phone: +47 62347000
E-mail: cert@moelven.com
Web: www.moelven.com

5. System of assessment and verification of constancy of performance of the product

System 2+

6. Certification

The notified body Norsk Trelastkontroll (identification number 1070) has performed an initial inspection of the manufacturing plants and of their factory production control and performs continuous surveillance, assessment and evaluation of our factory production controls. Norsk Trelastkontroll has issued **CE Certificate of Factory Production Control No. 1070 – CPR – 137.**

<i>Documentname</i> Declaration of performance Machine or visually strength graded structural timber	<i>Document no.</i> 137- 20190422	<i>Page</i> 2 of 2
<i>Prepared by</i> Odd Midtmoen	<i>Version</i> 1	
<i>Approved by</i> Per Skreden	<i>Replaces edition</i>	<i>Date</i> 2019-04-22

7. Declared performance

Essential characteristics	Declared performance
Species/ Spp. group	WPPA (Whitewood/ Norway Spruce/ Picea abies) or PNSY (Redwood/ Scots Pine/ Pinus sylvestris)
Growth area	NE Northern Europe
Range of thickness	24 – 100 mm
Range of width	75 – 300 mm
Surface finish	Sawn or planed
Grading	Dry graded
Strength, stiffness and density	Up to including C30 according to EN 338
Durability	4 (according to NS EN 350-2)
Reaction to fire	D-s2, d0
Release of dangerous substances	NPD (no performance detected)

Declaration of products as stated in no.1 and no. 2, is in accordance with characteristics as stated in no. 7. This declaration of performance is issued at own responsibility by the manufacturer, as stated no 4.

Moelv 2019-04-22

.....
Signature